

## **Push Latch**

## For wood doors and drawers







Spring force [N] (released) Spring force [N] (loaded) Item number 10 20 915-0X59 ---> 381

**Push Latch** 

Push Latch




With bumper

With bumper

With bumper 13 27 915-0320 ---> 381 20 381 With magnet 10 915-0D22 ----> Linear m. plate 915-4175 ---> 381 Cruciform m. plate 915-4183 ---> 381













915-0D22-381-K1 915-0D22-381-K2






200 Sets



Fixing screws for mounting plates



200 Pcs


Cruciform mounting plate

Euro screws 821-6323-050

Made of steel and plastic



5000 Pcs



Chipboard screws 820-6328-050



10000 Pcs

Accessories for Push Latch with magnet (Nickel plated steel)

Counter plate self adhesive







**915-7159-050** 500 Pcs









 $A = \emptyset 10 B = \emptyset 5$ 

915-7196-050 500 Pcs





















- · Effortless opening with just a light touch
- Depth adjustment ensures reliable closing and consistent performance in case of inaccurate drilling
- · 'Safety click' feature for easy detachment of the mechanism from its mounting plate





PushOpen with bumper works with standard hinge PushOpen with magnet works with reverse spring or unsprung hinges Door adjustment





Depth adjustment +4.5/-1mm

Drilling pattern Dimensions Depth adjustment












## Positioning



Close to the 'touch opening point' on the side opposite to hinges



On the cabinet side; gap between drawer and cabinet side 12mm min



On the drawer bottom; in the middle of drawer